Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



SECTION 1: Identification

1.1. Identification

Product form

Mixture

Product name

Dk Pool Blue ISO

Product code

US1040736XX

1.2 Recommended use and restrictions on use

Use of the substance/mixture

: Product for industrial use only

1.3. Supplier

LyondellBasell Advanced Polymers, Inc.

LyondellBasell Tower, Suite 300

1221 McKinney St.

P.O. Box 2583

Houston, TX 77252-2583

Customer service phone: 1-800-54-RESIN

Regulatory information: ASI-Amer.Regulatory.Requests@lyondellbasell.com

1.4. Emergency telephone number

Emergency number

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or

Within USA and Canada: 1-800-424-9300 CCN13495

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US and GHS-Canada classification

Flammable liquids, Category 3 Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2 Sensitisation - Skin, category 1

Specific target organ toxicity -- Single exposure, Category

3, Respiratory tract irritation

Specific target organ toxicity — Repeated exposure, Category 1

Flammable liquid and vapour.

Causes skin irritation. Causes serious eve irritation.

May cause an allergic skin reaction. May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

2.2. GHS Label elements, including precautionary statements

GHS-US and GHS-Canada labelling

Hazard pictograms (GHS-US and GHS-Canada):







Signal word (GHS-US and GHS-Canada)

: Danger

Hazard statements (GHS-US and GHS-Canada):

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US and GHS-

Canada)

Keep aw ay fromheat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. heat, sparks, open flames, hot surfaces

Keep cool.

Do not breathe dust, fume, gas, mist, spray, vapours.

Wash face, hands, hands, forearms and face thoroughly after handling

Avoid release to the environment.

12/02/2020

EN (English)

1/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



Wear eye protection, face protection, protective gloves.

Immediately call a doctor, a POISON CENTER.

In case of fire: Use ABC-pow der, carbon dioxide (CO2), dry extinguishing pow der, dry sand,

foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to an approved waste disposal plant.

Other hazards which do not result in classification 2.3.

No additional information available

Unknown acute toxicity (GHS-US and GHS-Canada) 2.4.

Not applicable

SECTION 3: Composition/information on ingredients

Substances 3.1.

Not applicable

3.2. **Mixtures**

Name	Product identifier	%
Styrene	(CAS No.) 100-42-5	30 - 60
Talc, Magnesium Silicate	(CAS No.) 14807-96-6	5 - 10
Titanium Dioxide	(CAS No.) 13463-67-7	5 - 10
Limestone	(CAS No.) 1317-65-3	1 - 5
2-Methy I-2-propenoic acid, methy I ester	(CAS No.) 80-62-6	1 - 5

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Des	cription of	first aid	measures

: Move the affected person away from the contaminated area. Immediately consult a First-aid measures general

doctor/medical service. If possible, show him this sheet. Failing this, show him the packaging or

label. Do not leave affected person unattended.

Call a physician immediately. If unconscious place in recovery position and seek medical First-aid measures after inhalation

After contact with skin, take off immediately all contaminated clothing, and wash immediately First-aid measures after skin contact

with plenty of water. Rinse immediately with plenty of water for 15 minutes. If symptoms persist,

call a physician.

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately and First-aid measures after eye contact

thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). If eye irritation

persists, consult a specialist.

In all cases of doubt, or when symptoms persist, seek medical advice. IF SWALLOWED: rinse First-aid measures after ingestion

mouth. Do NOT induce vomiting. Do not give milk.

Most important symptoms and effects (acute and delayed) 4.2.

: May cause respiratory irritation. Symptoms/effects afterinhalation

Symptoms/effects after skin contact Skin irritation, dermatitis and sensitisation. May cause sensitisation of susceptible persons by

skin contact.

: Causes serious eye irritation. Symptoms/effects after eye contact

: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Symptoms/effects afteringestion

Immediate medical attention and special treatment, if necessary 4.3.

If you feel unwell, seek medical advice.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media 5.1.

: Alcohol resistant foam. dry chemical pow der. Carbon dioxide. Suitable extinguishing media

Unsuitable extinguishing media : high volume water jet.

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



5.2. Specific hazards arising from the chemical

Fire hazard : Do not allow run-off from fire fighting to enter drains or water courses.

Reactivity : Stable under normal conditions.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Comply with local regulations for disposal.

Protection during firefighting : In case of fire: Wear self-contained breathing apparatus.

Other information : Use w ater spray/stream to protect personnel and to cool endangered containers. Collect

contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

: Wear suitable protective clothing.

Emergency procedures : Remove all sources of ignition. Ensure adequate ventilation. Evacuate personnel to a safe

area. Special attention should be given to low areas/pits where flammable vapours can

accumulate.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sew ers and public w aters. Notify authorities if liquid enters sewers or public w aters.

6.3. Methods and material for containment and cleaning up

For containment

: Collect the residue by means of a non-combustible absorbent material. Collect all w aste in suitable and labelled containers and dispose according to local legislation.

Methods for cleaning up

: Collect spillage. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid-or universal binding agents). Store in a well-ventilated place. Keep container tightly closed.

6.4. Reference to other sections

See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Use isolated drainage to prevent discharge to soil. Take precautionary measures against static discharge. The product may charge electrostatically: use earthling leads when transferring from one container to another. In order to rule out potential electrostatic discharge production, the

systemmust be adequately grounded.

Precautions for safe handling

: Do not exceed the occupational exposure limits (OEL). Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust. Provide good ventilation in process area to prevent formation of vapour.

: Do no eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Hygiene measures

: Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened should be properly resealed and kept upright to prevent leakage.

Storage temperature

: < 25 °C

Heat and ignition sources

: This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g, static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been. Explosion-free electrical equipment and lighting with earth. Electrical equipment should be protected to the appropriate standard.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Limestone (1317-65-3)		
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable dust)

12/02/2020 EN (English) 3/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020 Version: 15.2



Limestone (1317-65-3)		of the law street transfer of
NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³
Talc, Magnesium Silica	ite (14807-96-6)	
ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (ppm)	20 mppcf
OSHA	Remark (OSHA)	(3) See Table Z-3.
IDLH	US IDLH (mg/m³)	1000 mg/m³
NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³
Canada (Quebec)	VEMP (mg/m³)	3 mg/m³
Canada (Quebec)	Notations and remarks	(la poussière respirable)
Alberta	OEL TWA (mg/m³)	2 mg/m³
Alberta	Notations and remarks	(respirable particulate)
British Columbia	OEL TWA (mg/m³)	2 mg/m³ (Containing no asbestos fibres, Respirable)
Ontario	OEL TWA (mg/m³)	2 mg/m ³
		2 119/111
2-Methyl-2-propenoic a ACGIH	acid, m ethyl ester (80-62-6) ACGIH TWA (mg/m³)	205 mg/m³
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (mg/m³)	410 mg/m³
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; body w eight eff; DSEN; RSEN; A4 (Not classifiable as a Human Carcinogen: Agents w hich cause concern that they could be carcinogenic for humans but w hich cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)
OSHA	OSHA PEL (TWA) (mg/m³)	410 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	1000 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	410 mg/m³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
Canada (Quebec)	VEMP (mg/m³)	410 mg/m³
Canada (Quebec)	VEMP (ppm)	100 ppm
Alberta	OEL STEL (mg/m³)	410 mg/m³
Alberta	OEL STEL (ppm)	100 ppm
Alberta	OEL TWA (mg/m³)	205 mg/m³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL TWA (mg/m³)	100 mg/m³
British Columbia	OEL TWA (ppm)	50 ppm
British Columbia	Notations and remarks	S
Styrene (100-42-5)		
ACGIH	ACGIH TWA (mg/m³)	85 mg/m³
ACGIH	ACGIH TWA (ppm)	20 ppm
		170 mg/m³

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



Styrene (100-42-5)		
ACGIH	ACGIH STEL (ppm)	40 ppm
ACGIH	Remark (ACGIH)	CNS impair; URT irr; peripheral
OSHA	OSHA PEL (TWA) (mg/m³)	420 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL C [ppm]	
OSHA		200 ppm
OSHA	Remark (OSHA)	(Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 600 ppm 5 mins in any 3 hrs.)
IDLH	US IDLH (ppm)	700 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	215 mg/m³
NIOSH	NIOSH REL TWA [ppm]	50 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	425 mg/m³
NIOSH	NIOSH REL STEL [ppm]	100 ppm
Canada (Quebec)	VECD (mg/m³)	426 mg/m³
(440200)	(1.g/m)	425 mg/m³ (peau, C3)
Canada (Quebec)	VECD (ppm)	100 ppm
Canada (Quebec)	VEMP (mg/m³)	213 mg/m³
Canada (Quebec)	VEMP (ppm)	50 ppm
Alberta	OEL STEL (mg/m³)	170 mg/m³
Alberta	OEL STEL (ppm)	40 ppm
Alberta	OEL TWA (mg/m³)	85 mg/m³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL STEL (ppm)	75 ppm
British Columbia	OEL TWA (ppm)	50 ppm
British Columbia	Notations and remarks	2B
Ontario	OEL STEL (ppm)	100 ppm
Ontario	OEL TWA (ppm)	35 ppm
Titanium Dioxide (1346	3-67-7)	
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
ACGIH	Remark (ACGIH)	LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to w orker exposure. Available epidemiologic studies do not confirman increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³
IDLH	US IDLH (mg/m³)	5000 mg/m³
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³
Canada (Quebec)	Notations and remarks	(la poussière totale), (note1)
Alberta	OEL TWA (mg/m³)	10 mg/m³
Alberta	Notations and remarks	3
British Columbia	OEL TWA (mg/m²)	10 mg/m³
British Columbia	Notations and remarks	2B

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



8.2. Appropriate engineering controls

: Do not empty into drains. Environmental exposure controls

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:

Chemical resistant safety shoes. Overall.

Hand protection:

Wear suitable gloves. PVC gloves. A waterproof cream can protect exposed skin parts. Do not use if contact has already taken place. In case of reutilization, clean gloves before taking off and store in well-aired place. Before removing gloves clean them with soap and water. Protective gloves have to be replaced at the first sign of deterioration.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Safety glasses with side shields. Do not wear contact lenses

Skin and body protection:

Wear anti-static footw ear and clothing. Tight protective clothing required. Only wear fitting, comfortable and clean protective clothing. Wash clothing before re-using. Avoid contact with skin. May cause sensitisation of susceptible persons by skin contact

Respiratory protection:

In case of insufficient ventilation, we are suitable respiratory equipment. If excessive exposure exists, use only approved air-purifying or supplied air respirator operated in a positive pressure mode. Consult supplier for specific recommendations

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

: Liquid Physical state

: BUE - Blue

Odour : Pungent

Odour threshold No data available No data available pH : No data available Melting point No data available Freezing point

: 100 °C Boiling point 28.33 °C Flash point

: No data available Relative evaporation rate (butylacetate=1) Flammability (solid, gas) : No data available No data available Vapour pressure

: 4,5 Relative vapour density at 20 °C

Relative density : No data available Solubility Water: Negligible : No data available Log Pow Self ignition temperature No data available : No data available Decomposition temperature $> 20.5 \text{ mm}^2/\text{s}$ Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive limits : No data available Explosive properties Oxidising properties : No data available

9.2. Other information

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agents. Peroxides.

10.6. Hazardous decomposition products

Stable under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Styrene (100-42-5)	
LD50 oral rat	5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE US (oral)	5000 mg/kg bodyw eight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	11,8 mg/l/4h
ATE US (dust,mist)	1,5 mg/l/4h

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation. Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Talc, Magnesium Silicate (14807-96-6)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Tw elfth Report - Items under consideration
2-Methyl-2-propenoic acid, methyl ester (80-	-62-6)
IARC group	3 - Not classifiable
Styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes
Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication, Carcinogen	Yes

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

12/02/2020 EN (English) 7/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



: Causes damage to organs through prolonged or repeated exposure. STOT-repeated exposure

: Not classified Aspiration hazard

Symptoms/effects afterinhalation : May cause respiratory irritation.

: Skin irritation, dermatitis and sensitisation. May cause sensitisation of susceptible persons by Symptoms/effects afterskin contact

skin contact.

: Causes serious eye irritation. Symptoms/effects after eye contact

: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Symptoms/effects afteringestion

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. How ever, tests with other laboratory animals, such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to

titanium dioxide

SECTION 12: Ecological information

Toxicity

Other information

Styrene (100-42-5)	
LC50 fish 1	4,02 mg/l Pimephales promelas (fathead minnow)
EC50 Daphnia 1	4,7 mg/l Daphnia magna.
NOEC chronic crustacea	1,01 mg/l Daphnia magna (Water flea)
Titanium Dioxide (13463-67-7)	
ErC50 (algae)	> 100 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Dk Pool Blue ISO	
Persistence and degradability	No data available.

Bioaccum ulative potential 12.3.

Dk Pool Blue ISO	
Bioaccumulative potential	No data available.

Styrene (100-42-5)	
Log Pow	3

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

: No data available. Other adverse effects

SECTION 13: Disposal considerations

13.1. Disposal methods

: Disposal must be done according to official regulations. Hazardous waste. Solvent. Regional legislation (w aste)

: Do not allow to enter into surface water or drains. Sew age disposal recommendations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2

Waste disposal recommendations

lyondellbasell

: Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packaging in the same way as the product itself.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description

UN-No.(DOT)

Proper Shipping Name (DOT)

Class (DOT)

Packing group (DOT)

Hazard labels (DOT)

: UN1866 Resin solution (flammable), 3, III

UN1866

: Resin solution

flammable

3 - Class 3 - Flammable and combustible liquid 49 CFR 173,120

: III - Minor Danger 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Special Provisions (49 CFR 172.102)

: 173 : 242

> : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173,242 of this subchapter are applicable.

B52 - Notw ith standing the provisions of 173.24b of this subchapter, non-reclosing pressure

relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail: 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location

: A - The material may be stow ed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory with status Active

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-Methyl-2-propenoic acid, methyl ester	CAS No 80-62-6	SARA Section 313 - Emission Reporting 1,0%	1 - 5%
Styrene	CAS No 100-42-5	SARA Section 313 - Emission Reporting 0,1%	30 - 60%

15.2. US State regulations



This product can expose you to Quartz (SiO2): 1-10% fine fraction, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)
Quartz (SiO2): 1-10% fine fraction(14808-60-7)	X				
Styrene(100-42-5)	X				27 μg/day
Titanium Dioxide(13463-67-7)	Х				
Naphthalene(91-20-3)	X				5,8 µg/day
ethylbenzene(100-41- 4)	Х				54 μg/day (inhalation)
Cumene(98-82-8)	X				

Limestone (1317-65-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Talc, Magnesium Silicate (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. Pennsylvania RTK (Right to Know) List

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



2-Methyl-2-propenoic acid, methyl ester (80-62-6)

- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Illinois Toxic Air Contaminants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundw ater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Styrene (100-42-5)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Illinois Toxic Air Contaminant Carcinogens
- U.S. Illinois Toxic Air Contaminants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Primary Drinking Water Standards Maximum Contaminant Levels MCLs
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey Water Quality Ground Water Quality Criteria
 U.S. New Jersey Water Quality Practical Quantitation Levels (PQLs)
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- U.S. Pennsylvania Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Titanium Dioxide (13463-67-7)

- U.S. Illinois Toxic Air Contaminant Carcinogens
- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Federal regulations

All chemical substances in this product are listed or excluded from listing on the Canadian Domestic Substances List (DSL) or the Canadian Non-Domestic Substances List (NDSL) inventory.

SECTION 16: Other information

Revision date : 11/17/2020

Version : 15.2

Abbreviations and acronyms:

12/02/2020 EN (English) 11/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/17/2020

Version: 15.2



REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006		
SVHC	Substance of very high concern		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
IMDG	International Maritime Dangerous Goods		
IATA	International Air Transport Association		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
MARPOL 73/78	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("MARPOL" is short for marine pollution and 73/78 short for the years 1973 and 1978.)		
IBC	The International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk		
OSHA	Occupational Safety & Health Administration		
TWA	Time Weighted Average		
STEL	Occupational Exposure Limits - Short Term Exposure Limits (STELs)		
ACGIH	American Conference of Governement Industrial Hygienists		
TLV	Threshold Limit Value		
IARC	International Agency for Research on Cancer		

Version	Indication of changes	Change	Comments
15.1	1.4 > Emergency phone number	Modified	
15.2	11.1 > Schulman Special Case Components	Modified	

Information in this document is accurate to the best of our know ledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any w arranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell w ebsite at:

https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/

The Trade Name referenced in section 1 is a trademark ow ned or used by the LyondellBasell family of companies.