

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : NEUTRAL ISO FDA APPROVABLE
Product code : US1045656XX

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Product for industrial use only

1.3. Supplier

LyondellBasell Advanced Polymers, Inc.

LyondellBasell Tower, Suite 300

1221 McKinney St.

P.O. Box 2583

Houston, TX 77252-2583

Customer service phone : 1-800-54-RESIN

Regulatory information: ASI-Amer.Regulatory.Requests@lyondellbasell.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300 CCN13495
Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US and GHS-Canada classification

Flammable liquids Category 3	Flammable liquid and vapor
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction
Reproductive toxicity Category 2	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 1	Causes damage to organs through prolonged or repeated exposure

2.2. GHS Label elements, including precautionary statements

GHS-US and GHS-Canada labeling

Hazard pictograms (GHS-US and GHS-Canada) :



Signal word (GHS-US and GHS-Canada) : Danger

Hazard statements (GHS-US and GHS-Canada) : Flammable liquid and vapor
Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
May cause respiratory irritation
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US and GHS-Canada) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, sparks, open flames, hot surfaces
Keep cool.
Do not breathe dust, fume, gas, mist, spray, vapors.
Wash face, hands, hands, forearms and face thoroughly after handling

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Avoid release to the environment.
Wear eye protection, face protection, protective gloves
Immediately call a doctor, a POISON CENTER.
In case of fire: Use ABC-powder, carbon dioxide (CO₂), dry extinguishing powder, dry sand, foam to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS-US and GHS-Canada)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Styrene	(CAS No) 100-42-5	30 - 60
Talc, Magnesium Silicate	(CAS No) 14807-96-6	5 - 10
Limestone	(CAS No) 1317-65-3	1 - 5
2-Methyl-2-propenoic acid, methyl ester	(CAS No) 80-62-6	1 - 5
Cobalt 2-Ethylhexanoate	(CAS No) 136-52-7	0.1 - 1

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Move the affected person away from the contaminated area. Immediately consult a doctor/medical service. If possible, show him this sheet. Failing this, show him the packaging or label. Do not leave affected person unattended.
First-aid measures after inhalation	: Call a physician immediately. If unconscious place in recovery position and seek medical advice.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Rinse immediately with plenty of water for 15 minutes. If symptoms persist, call a physician.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). If eye irritation persists, consult a specialist.
First-aid measures after ingestion	: In all cases of doubt, or when symptoms persist, seek medical advice. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Do not give milk.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Skin irritation, dermatitis and sensitization. May cause sensitization of susceptible persons by skin contact.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Immediate medical attention and special treatment, if necessary

If you feel unwell, seek medical advice.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. dry chemical powder. Carbon dioxide.
------------------------------	--

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Unsuitable extinguishing media : high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Do not allow run-off from fire fighting to enter drains or water courses.

Reactivity : Stable under normal conditions.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Comply with local regulations for disposal.

Protection during firefighting : In case of fire: Wear self-contained breathing apparatus.

Other information : Use water spray/stream to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing.

Emergency procedures : Remove all sources of ignition. Ensure adequate ventilation. Evacuate personnel to a safe area. Special attention should be given to low areas/pits where flammable vapors can accumulate.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect the residue by means of a non-combustible absorbent material. Collect all waste in suitable and labeled containers and dispose according to local legislation.

Methods for cleaning up : Collect spillage. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Store in a well-ventilated place. Keep container tightly closed.

6.4. Reference to other sections

See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Use isolated drainage to prevent discharge to soil. Take precautionary measures against static discharge. The product may charge electrostatically: use earthing leads when transferring from one container to another. In order to rule out potential electrostatic discharge production, the system must be adequately grounded.

Precautions for safe handling : Do not exceed the occupational exposure limits (OEL). Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust. Provide good ventilation in process area to prevent formation of vapor.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened should be properly resealed and kept upright to prevent leakage.

Storage temperature : < 25 °C

Heat-ignition : This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been. Explosion-proof electrical equipment and grounded lighting. Electrical equipment should be protected to the appropriate standard.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Styrene (100-42-5)		
ACGIH	ACGIH TWA (mg/m³)	85 mg/m³
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (mg/m³)	170 mg/m³
ACGIH	ACGIH STEL (ppm)	40 ppm
ACGIH	Remark (ACGIH)	CNS impair; URT irr; peripheral
OSHA	OSHA PEL (TWA) (mg/m³)	420 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm
OSHA	Remark (OSHA)	(Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 600 ppm 5 mins. in any 3 hrs.)
IDLH	US IDLH (ppm)	700 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	215 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	425 mg/m³
NIOSH	NIOSH REL (STEL) (ppm)	100 ppm
Limestone (1317-65-3)		
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable dust)
NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)
Talc, Magnesium Silicate (14807-96-6)		
ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (ppm)	20 mppcf
OSHA	Remark (OSHA)	(3) See Table Z-3.
IDLH	US IDLH (mg/m³)	1000 mg/m³
NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³
Cobalt 2-Ethylhexanoate (136-52-7)		
Not applicable		
2-Methyl-2-propenoic acid, methyl ester (80-62-6)		
ACGIH	ACGIH TWA (mg/m³)	205 mg/m³
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (mg/m³)	410 mg/m³
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; body weight eff; DSEN; RSEN; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)
OSHA	OSHA PEL (TWA) (mg/m³)	410 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	1000 ppm

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



2-Methyl-2-propenoic acid, methyl ester (80-62-6)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	410 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm

8.2. Appropriate engineering controls

Environmental exposure controls : Do not empty into drains.

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:

Chemical resistant safety shoes. Overall.

Hand protection:

Wear suitable gloves. PVC gloves. A waterproof cream can protect exposed skin parts. Do not use if contact has already taken place. In the case of wanting to use the gloves again, clean them before taking off and air them well. Before removing gloves clean them with soap and water. Replace when worn.

Eye protection:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Safety glasses with side shields. Do not wear contact lenses

Skin and body protection:

Wear anti-static footwear and clothing. Tight protective clothing required. Only wear fitting, comfortable and clean protective clothing. Wash clothing before re-using. Avoid contact with skin. May cause sensitization of susceptible persons by skin contact

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. If excessive exposure exists, use only approved air-purifying or supplied air respirator operated in a positive pressure mode. Consult supplier for specific recommendations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: N/A - Not available
Odor	: Pungent
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: 28.33 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: 4.5
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.3. Possibility of hazardous reactions

vapors may form explosive mixture with air.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agents. Peroxides.

10.6. Hazardous decomposition products

Stable under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Styrene (100-42-5)	
LD50 oral rat	5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Talc, Magnesium Silicate (14807-96-6)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Twelfth Report - Items under consideration

2-Methyl-2-propenoic acid, methyl ester (80-62-6)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Skin irritation, dermatitis and sensitization. May cause sensitization of susceptible persons by skin contact.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

Styrene (100-42-5)	
LC50 fish 1	4.02 mg/l Pimephales promelas (fathead minnow)
EC50 Daphnia 1	4.7 mg/l Daphnia magna.
NOEC chronic crustacea	1.01 mg/l Daphnia magna (Water flea)

12.2. Persistence and degradability

NEUTRAL ISO FDA APPROVABLE	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

NEUTRAL ISO FDA APPROVABLE	
Bioaccumulative potential	No data available.
Styrene (100-42-5)	
Log Pow	3

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations. Hazardous waste. Solvent.
Sewage disposal recommendations	: Do not allow to enter into surface water or drains.
Waste disposal recommendations	: Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1866 Resin solution (flammable), 3, III
UN-No.(DOT)	: UN1866
Proper Shipping Name (DOT)	: Resin solution flammable
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Hazard labels (DOT)

: 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)

: 173

DOT Packaging Bulk (49 CFR 173.xxx)

: 242

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx)

: 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: 220 L

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Emergency Response Guide (ERG) Number

: 127

Transportation of Dangerous Goods

Not regulated

Not regulated

Transport by sea

Not regulated

Not regulated

Air transport

Not regulated

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory with status Active

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Styrene	CAS No 100-42-5	SARA Section 313 - Emission Reporting 0.1%	30 - 60%
2-Methyl-2-propenoic acid, methyl ester	CAS No 80-62-6	SARA Section 313 - Emission Reporting 1.0%	1 - 5%

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



15.2. US State regulations

⚠ WARNING: This product can expose you to Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)
Styrene(100-42-5)	X				27 µg/day
Quartz (SiO ₂): 1-10% fine fraction(14808-60-7)	X				
Naphthalene(91-20-3)	X				5.8 µg/day
ethylbenzene(100-41-4)	X				54 µg/day (inhalation)
Cumene(98-82-8)	X				

Styrene (100-42-5)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Illinois - Toxic Air Contaminants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Talc, Magnesium Silicate (14807-96-6)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



2-Methyl-2-propenoic acid, methyl ester (80-62-6)

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Illinois - Toxic Air Contaminants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

15.3. Canadian Federal regulations

All chemical substances in this product are listed or excluded from listing on the Canadian Domestic Substances List (DSL) or the Canadian Non-Domestic Substances List (NDSL) inventory.

SECTION 16: Other information

Revision date : 05/29/2020

Version : 7.2

Abbreviations and acronyms:

REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SVHC	Substance of very high concern
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
MARPOL 73/78	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("MARPOL" is short for marine pollution and 73/78 short for the years 1973 and 1978.)
IBC	The International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
OSHA	Occupational Safety & Health Administration
TWA	Time Weighted Average
STEL	Occupational Exposure Limits - Short Term Exposure Limits (STELs)
ACGIH	American Conference of Government Industrial Hygienists
TLV	Threshold Limit Value
IARC	International Agency for Research on Cancer

Version	Indication of changes	Change	Comments
7.1	1.3 > Company	Added	
7.1	11.1 > Styrene > Acute toxicity	Modified	

NEUTRAL ISO FDA APPROVABLE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/29/2020

Version: 7.2



Version	Indication of changes	Change	Comments
7.1	12.1 > Styrene > LC50	Modified	
7.1	12.1 > Cobalt 2-Ethylhexanoate > LC50	Removed	
7.1	12.1 > Styrene > EC50	Modified	
7.1	12.1 > Cobalt 2-Ethylhexanoate > EC50	Removed	
7.1	12.1 > Styrene > ErC50	Removed	
7.1	12.1 > Styrene > NOEC	Modified	
7.1	12.1 > Cobalt 2-Ethylhexanoate > NOEC	Removed	
7.2	1.4 > Emergency phone number	Modified	

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at:

<https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/>

The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

