Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15 1



SECTION 1: Identification

1.1. Identification

Product name

: 82-103960 White U.S. Gelcoat

Product form

: Mixture

Product code

: US1040530XX

1.2. Recommended use and restrictions on use

Use of the substance/mixture

: Product for industrial use only

Prohibited for use

: Applications involving permanent implantation into the body

European class III medical devices FDA Class III medical devices

Health Canada class IV Medical Devices Life-sustaining medical applications

1.3. Supplier

LyondellBasell Advanced Polymers, Inc.

LyondellBasell Tower, Suite 300

1221 McKinney St.

P.O. Box 2583

Houston, TX 77252-2583

Customer service phone: 1-800-54-RESIN

Regulatory information: ASI-Amer.Regulatory.Requests@lyondellbasell.com

1.4. Emergency telephone number

Emergency number

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or

Night

Within USA and Canada: 1-800-424-9300 CCN13495

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US and GHS-Canada classification

Flammable liquids, Category 3

Flammable liquid and vapour.

Skin corrosion/irritation, Category 2

Causes skin irritation.

Serious eye damage/eye irritation, Category 2

Causes serious eye irritation.

Sensitisation - Skin, category 1

May cause an allergic skin reaction.

Reproductive toxicity, Category 1B

May damage fertility or the unborn child.

Reproductive toxicity, Additional category, Effects on or May cause harm to breast-fed children.

via lactation

Specific target organ toxicity — Single exposure,

May cause respiratory irritation.

Category 3, Respiratory tract irritation

Specific target organ toxicity — Repeated exposure,

Causes damage to organs through prolonged or repeated exposure.

Category 1

2.2. GHS Label elements, including precautionary statements

GHS-US and GHS-Canada labelling

Hazard pictograms (GHS-US and GHS-Canada)







Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1

Signal word (GHS-US and GHS-Canada)

Hazard statements (GHS-US and GHS-Canada)

: Danger

: Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.

May damage fertility or the unborn child. May cause harm to breast-fed children.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US and GHS-

Canada)

Keep aw ay fromheat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

lyondellbasell

heat, sparks, open flames, hot surfaces

Keep cool.

Do not breathe dust, fume, gas, mist, spray, vapours.

Wash face, hands, hands, forearms and face thoroughly after handling

Avoid release to the environment.

Wear eye protection, face protection, protective gloves.

Immediately call a doctor, a POISON CENTER.

In case of fire: Use ABC-pow der, carbon dioxide (CO2), dry extinguishing pow der, dry sand,

foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS-US and GHS-Canada)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Styrene	CAS No.: 100-42-5	30 – 60
Titanium Dioxide	CAS No.: 13463-67-7	10 – 30
2-Methyl-2-propenoic acid, methyl ester	CAS No.: 80-62-6	5 – 10
Talc, Magnesium Silicate	CAS No.: 14807-96-6	1 – 5
Limestone	CAS No.: 1317-65-3	1 – 5
Methanol	CAS No.: 67-56-1	0,1 – 1
Hexanoic acid, 2-ethyl-, potassiumsalt (1:1)	CAS No.: 3164-85-0	0,1 – 1
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-	CAS No.: 77-99-6	0,1 – 1

Full text of hazard classes and H-statements; see section 16

04/05/2021 EN (English) 2/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

: Move the affected person away from the contaminated area. Immediately consult a doctor/medical service. If possible, show him this sheet. Failing this, show him the packaging or

label. Do not leave affected person unattended.

: Call a physician immediately. If unconscious place in recovery position and seek medical advice.

: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Rinse immediately with plenty of water for 15 minutes. If symptoms persist, call a physician.

: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). If eye irritation persists, consult a specialist.

: In all cases of doubt, or when symptoms persist, seek medical advice. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Do not give milk.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation

Symptoms/effects afterskin contact

: May cause respiratory irritation.

: Skin irritation, dermatitis and sensitisation. May cause sensitisation of susceptible persons by

skin contact.

Symptoms/effects after eye contact

Symptoms/effects afteringestion

Causes serious eye irritation.

May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Immediate medical attention and special treatment, if necessary

If you feel unwell, seek medical advice.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

: Alcohol resistant foam, dry chemical pow der. Carbon dioxide.

Unsuitable extinguishing media

: high volume water jet.

5.2. Specific hazards arising from the chemical

: Do not allow run-off from fire fighting to enter drains or water courses.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: Comply with local regulations for disposal.

Protection during firefighting

: In case of fire: Wear self-contained breathing apparatus.

Other information

: Use water spray/stream to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

: Wear suitable protective clothing.

Emergency procedures

: Remove all sources of ignition. Ensure adequate ventilation. Evacuate personnel to a safe area. Special attention should be given to low areas/pits where flammable vapours can accumulate.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sew ers and public w aters. Notify authorities if liquid enters sewers or public w aters.

3/16 04/05/2021 EN (English)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



6.3. Methods and material for containment and cleaning up

For containment

: Collect the residue by means of a non-combustible absorbent material. Collect all waste in suitable and labelled containers and dispose according to local legislation.

Methods for cleaning up

: Collect spillage. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Store in a well-ventilated place. Keep container tightly closed.

6.4. Reference to other sections

See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Use isolated drainage to prevent discharge to soil. Take precautionary measures against static discharge. The product may charge electrostatically: use earthling leads when transferring from one container to another. In order to rule out potential electrostatic discharge production, the systemmust be adequately grounded.

Precautions for safe handling

: Do not exceed the occupational exposure limits (OEL). Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

: Do no eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened should be properly resealed and kept upright to prevent leakage.

Storage temperature

: < 25 °C

Heat and ignition sources

: This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g, static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been. Explosion-free electrical equipment and lighting with earth. Electrical equipment should be protected to the appropriate standard.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

82-103960 White U.S. Gelcoat	seamanista varia algorido e Perud Parent Aprila de Artido de C	Total and the second se
No additional information available		
Hexanoic acid, 2-ethyl-, potassiur	n salt (1:1) (3164-85-0)	Sook gelen bringes i
No additional information available		
Limestone (1317-65-3)	Cold (NO Section 2015) as which to differ the different fields the property distributions of the	
USA - OSHA - Occupational Exposure	e Limits	
OSHA PEL TWA [1]	15 mg/m³ (total dust) 5 mg/m³ (respirable dust)	
USA - NIOSH - Occupational Exposur	e Limits	
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)	

04/05/2021 EN (English) 4/16

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Talc, Magnesium Silicate (148	07-96-6)
USA - ACGIH - Occupational Expo	os ure Limits
ACGIH OEL TWA	2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
ACGIH chemical category	Not Classifiable as a Human Carcinogen containing no asbestos fibers
USA - OSHA - Occupational Expo	sure Limits
OSHA PEL TWA [2]	20 mppcf
Remark (OSHA)	(3) See Table Z-3.
USA - IDLH - Occupational Expos	ure Limits
IDLH	1000 mg/m³
USA - NIOSH - Occupational Expo	os ure Limits
NIOSH REL TWA	2 mg/m³
2-Methyl-2-propenoic acid, me	ethyl ester (80-62-6)
USA - ACGIH - Occupational Expo	os ure Limits
ACGIH OEL TWA	205 mg/m²
ACGIH OEL TWA [ppm]	50 ppm
ACGIH OEL STEL	410 mg/m³
ACGIH OEL STEL [ppm]	100 ppm
Remark (ACGIH)	URT & eye irr; body w eight eff; DSEN; RSEN; A4 (Not classifiable as a Human Carcinogen: Agents w hich cause concern that they could be carcinogenic for humans but w hich cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity w hich are sufficient to classify the agent into one of the other categories)
ACGIH chemical category	dermal sensitizer, Not Classifiable as a Human Carcinogen
USA - OSHA - Occupational Expo	sure Limits
OSHA PEL TWA [1]	410 mg/m²
OSHA PEL TWA [2]	100 ppm
USA - IDLH - Occupational Expos	ure Limits
IDLH [ppm]	1000 ppm
USA - NIOSH - Occupational Expo	os ure Limits
NIOSH REL TWA	410 mg/m³
NIOSH REL TWA [ppm]	100 ppm
Styrene (100-42-5)	
USA - ACGIH - Occupational Expo	osure Limits
ACGIH OEL TWA	85 mg/m²
ACGIH OEL TWA [ppm]	20 ppm
ACGIH OEL STEL	170 mg/m³

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Styrene (100-42-5)	
ACGIH OEL STEL [ppm]	40 ppm
Remark (ACGIH)	CNS impair; URT irr; peripheral
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indice	es e e e e e e e e e e e e e e e e e e
B⊟	400 mg/g creatinine (Medium: urine - Time: end of shift - Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific) 40 μg/l (Medium: urine - Time: end of shift - Parameter: Styrene)
USA - OSHA - Occupational Exposure Lim	nits
OSHA PEL TWA [1]	420 mg/m³
OSHA PEL TWA [2]	100 ppm
OSHA PEL C [ppm]	200 ppm
Remark (OSHA)	(Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 600 ppm 5 mins. in any 3 hrs.)
USA - IDLH - Occupational Exposure Limi	ts
IDLH [ppm]	700 ppm
USA - NIOSH - Occupational Exposure Lin	nits
NIOSH REL TWA	215 mg/m³
NIOSH REL TWA [ppm]	50 ppm
NIOSH REL STEL	425 mg/m³
NIOSH REL STEL [ppm]	100 ppm
Methanol (67-56-1)	MARIANI DESTRUMENTO CARRESONANTO CONTRA CONT
USA - ACGIH - Occupational Exposure Lir	nits
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	250 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA - ACGIH - Biological Exposure Indice	es
BEI	15 mg/l (Medium: urine - Time: end of shift - Parameter: Methanol (background, nonspecific
USA - OSHA - Occupational Exposure Lim	nits
OSHA PEL TWA [1]	260 mg/m³
OSHA PEL TWA [2]	200 ppm
USA - NIOSH - Occupational Exposure Lin	nits
NIOSH REL TWA	260 mg/m³
NIOSH REL TWA [ppm]	200 ppm
NIOSH REL STEL	325 mg/m³
NIOSH REL STEL [ppm]	250 ppm
US-NIOSH chemical category	Potential for dermal absorption

6/16 04/05/2021 EN (English)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



1,3-Propanediol, 2-ethyl-2-(hyd	droxymethyl)- (7	77-99-6)		
No additional information available				
Titanium Dioxide (13463-67-7)		The state of the s		
USA - ACGIH - Occupational Expo	sure Limits	-		
ACGIH OEL TWA		10 mg/m³		
Remark (ACGIH)		LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Hur carcinogenic in experimental animals at a relatively high dose, by route(s) of site(s), of histologic type(s), or by mechanism(s) that may not be relevant to Available epidemiologic studies do not confirman increased risk of cancer Available evidence does not suggest that the agent is likely to cause cancer under uncommon or unlikely routes or levels of exposure)	of administration, at owner exposure. in exposed humans.	
ACGIH chemical category		Not Classifiable as a Human Carcinogen		
USA - OSHA - Occupational Expo	sure Limits	•		
OSHA PEL TWA [1]		15 mg/m³		
USA - IDLH - Occupational Exposure Limits				
IDLH		5000 mg/m²		

8.2. Appropriate engineering controls

Environmental exposure controls

: Do not empty into drains.

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:

Chemical resistant safety shoes. Overall.

Hand protection:

Wear suitable gloves. PVC gloves. A waterproof cream can protect exposed skin parts. Do not use if contact has already taken place. In case of reutilization, clean gloves before taking off and store in well-aired place. Before removing gloves clean them with soap and water. Protective gloves have to be replaced at the first sign of deterioration.

Eye protection:

Emergency eye w ash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Safety glasses with side shields. Do not wear contact lenses

Skin and body protection:

Wear anti-static footwear and clothing. Tight protective clothing required. Only wear fitting, comfortable and clean protective clothing. Wash clothing before re-using. Avoid contact with skin. May cause sensitisation of susceptible persons by skin contact

Respiratory protection:

In case of insufficient ventilation, we are suitable respiratory equipment. If excessive exposure exists, use only approved air-purifying or supplied air respirator operated in a positive pressure mode. Consult supplier for specific recommendations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : WHI - w hite

04/05/2021 EN (English) 7/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1

Odour

: Pungent

Odour threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available Boiling point : 100 °C

Flash point : 100 °C
Flash point : 28,33 °C

Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) : No data available Vapour pressure : No data available

Relative vapour density at 20 °C : 4,5

Relative density : No data available Solubility Water: Negligible Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Self ignition temperature : No data available Decomposition temperature Viscosity, kinematic $> 20,5 \text{ mm}^2/\text{s}$ Viscosity, dynamic : No data available Explosive limits : No data available Explosive properties : No data available Oxidising properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agents. Peroxides.

10.6. Hazardous decomposition products

Stable under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Styrene (100-42-5)		
LD50 oral rat	5000 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
ATE US (oral)	5000 mg/kg bodyw eight	

04/05/2021 EN (English) 8/16



Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Styrene (100-42-5)			
ATE US (gases)		4500 ppmv/4h	
ATE US (vapours)		11,8 mg/l/4h	
ATE US (dust,mist)		1,5 mg/l/4h	
Methanol (67-56-1)			
LD50 oral rat		2528 mg/kg	
LD50 dermal rabbit		17100 mg/kg	
LC50 Inhalation - Rat		128,2 mg/l	
ATE US (oral)		100 mg/kg bodyw eight	
ATE US (dermal)		300 mg/kg bodyw eight	
ATE US (gases)		700 ppmv/4h	
ATE US (vapours)		3 mg/l/4h	
ATE US (dust,mist)		0,5 mg/l/4h	
1,3-Propanediol, 2-ethyl-2-(hy	droxymethyl)- (7	7-99-6)	
LD50 oral rat		14100 mg/kg	
ATE US (oral)		14100 mg/kg bodyw eight	
Titanium Dioxide (13463-67-7)		
LD50 oral rat		> 5000 mg/kg	
LD50 dermal rabbit		> 10000 mg/kg	
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation	:	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.	
Germ cell mutagenicity Carcinogenicity	:	Not classified Not classified	
Talc, Magnesium Silicate (148	307-96-6)		
IARC group		3 - Not classifiable	
National Toxicology Program (NTP)	Status	Evidence of Carcinogenicity, Tw elfth Report - Items under consideration	
2-Methyl-2-propenoic acid, m	ethyl ester (80-6	2-6)	
IARC group		3 - Not classifiable	
Styrene (100-42-5)			
IARC group		2B - Possibly carcinogenic to humans	
National Toxicology Program (NTP)	Status	Reasonably anticipated to be Human Carcinogen	
In OSHA Hazard Communication C	arcinogen list	Yes	
Titanium Dioxide (13463-67-7)		
IARC group		2B - Possibly carcinogenic to humans	
In OSHA Hazard Communication C	arcinogen list	Yes	
Reproductive toxicity	:	May damage fertility or the unborn child. May cause harm to breast-fed children.	
04/05/2021	EN	N (English) 9/16	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



STOT-single exposure

STOT-repeated exposure

Aspiration hazard

Symptoms/effects afterinhalation

Symptoms/effects after skin contact

Symptoms/effects after eye contact Symptoms/effects afteringestion

Other information

: May cause respiratory irritation.

: Causes damage to organs through prolonged or repeated exposure.

: Not classified

: May cause respiratory irritation.

: Skin irritation, dermatitis and sensitisation. May cause sensitisation of susceptible persons by

skin contact.

: Causes serious eye irritation.

: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. How ever, tests with other laboratory animals, such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide

SECTION 12: Ecological information

12.1. Toxicity

Styrene (100-42-5)	
LC50 - Fish [1]	4,02 mg/l Pimephales promelas (fathead minnow)
EC50 - Crustacea [1]	4,7 mg/l Daphnia magna.
NOEC chronic crustacea	1,01 mg/l Daphnia magna (Water flea)
Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l Lepomis macrochirus
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna.
ErC50 algae	22000 mg/l Selenastrum capricornutum (green algae)
NOEC chronic fish	7900 mg/l Oryzias latipes
Titanium Dioxide (13463-67-7)	n de la companya del companya de la companya del companya de la co
ErC50 algae	> 100 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

82-103960 White U.S. Gelcoat	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

82-103960 White U.S. Gelcoat			
Bioaccumulative potential	No data available.		
Styrene (100-42-5)			
Partition coefficient n-octanol/water (Log Pow) 3			
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6)			
BCF - Fish [1]	0,14		

04/05/2021 EN (English) 10/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)- (77-99-6)

Partition coefficient n-octanol/water (Log Pow)

-2.37

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects

: No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)

Sew age disposal recommendations

Waste disposal recommendations

- : Disposal must be done according to official regulations. Hazardous waste. Solvent.
- : Do not allow to enter into surface water or drains.
- Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packaging in the same way as the product itself.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)

UN-No.(DOT)

Proper Shipping Name (DOT)

Class (DOT)

Packing group (DOT) Hazard labels (DOT)

: UN1866

: Resin solution flammable

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

: UN1866 Resin solution (flammable), 3, III

III - Minor Danger : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

: 173 : 242

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notw ith standing the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail: 60 L

(49 CFR 173.27)

04/05/2021

11/16 EN (English)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stow age Location : A - The material may be stow ed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory with status Active

Chemical(s) subject to the reporting requirements of Section 313 or and 40 CFR Part 372.	r Title III of the Superf	und Amendments and Reauthorization	Act (SARA) of 1986		
2-Methyl-2-propenoic acid, methyl ester CAS No 80-62-6 SARA Section 313 - Emission 5 - 10% Reporting 1,0%					
Styrene	CAS No 100-42-5	SARA Section 313 - Emission Reporting 0.1%	30 - 60%		

15.2. US State regulations



This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)
Quartz (SiO2): 1-10% fine fraction(14808-60-7)	X				
Styrene(100-42-5)	Х				27 μg/day
Ethylene glycol(107- 21-1)		Х			
Acetaldehyde(75-07-0)	Х				90 μg/day (inhalation)
Ethylene Oxide(75-21-8)	Х	X	Х	X	2 μg/day
1,4-Dioxane(123-91-1)	Х				30 μg/day
Methanol(67-56-1)		X			
Titanium Dioxide(13463-67-7)	Х				
Naphthalene(91-20-3)	Х				5,8 µg/day
ethylbenzene(100-41- 4)	Х				54 μg/day (inhalation)
Cumene(98-82-8)	X				

04/05/2021 EN (English) 12/16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Limestone (1317-65-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Talc, Magnesium Silicate (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. Pennsylvania RTK (Right to Know) List

2-Methyl-2-propenoic acid, methyl ester (80-62-6)

- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Illinois Toxic Air Contaminants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Styrene (100-42-5)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Illinois Toxic Air Contaminant Carcinogens
- U.S. Illinois Toxic Air Contaminants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Primary Drinking Water Standards Maximum Contaminant Levels MCLs
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List

- U.S. New Jersey Water Quality Ground Water Quality Criteria
 U.S. New Jersey Water Quality Practical Quantitation Levels (PQLs)
 U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- U.S. Pennsylvania Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List U.S. Pennsylvania RTK (Right to Know) List

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Methanol (67-56-1)

- U.S. California Proposition 65 Maximum Allow able Dose Levels (MADL)
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Illinois Toxic Air Contaminants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey Water Quality Ground Water Quality Criteria
- U.S. New Jersey Water Quality Practical Quantitation Levels (PQLs)
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Titanium Dioxide (13463-67-7)

- U.S. Illinois Toxic Air Contaminant Carcinogens
- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Revision date
 : 03/05/2021

 Version
 : 15.1

Abbreviations and acronyms				
REA CH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006			
SVHC	Substance of very high concern			
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008			
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road			
IMDG	International Maritime Dangerous Goods			
IATA	International Air Transport Association			
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways			
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail			
MARPOL 73/78	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("MARPOL" is short for marine pollution and 73/78 short for the years 1973 and 1978.)			
IBC	The International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk			
OSHA	Occupational Safety & Health Administration			

04/05/2021 EN (English) 14/16

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Abbreviations	nd acronyms
TWA	Time Weighted Average
STEL	Occupational Exposure Limits - Short Term Exposure Limits (STELs)
ACGIH	American Conference of Governement Industrial Hygienists
TLV	Threshold Limit Value
IARC	International Agency for Research on Cancer
ED	Endocrine disrupting properties

Indication of changes:				
Version	Indication of changes	Change	Comments	
15.1	1.2 > Schulman Prohibited Uses	Added		
15.1	3.2 > Composition/information on ingredients > Styrene > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > Titanium Dioxide > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > 2- Methyl-2-propenoic acid, methyl ester > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > Talc, Magnesium Silicate > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > Limestone > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > Methanol > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > Hexanoic acid, 2-ethyl-, potassiumsalt (1:1) > Concentration	Modified		
15.1	3.2 > Composition/information on ingredients > 1,3- Propanediol, 2-ethyl-2-(hydroxymethyl)-> Concentration	Modified		
15.1	8.1 > Control parameters	Added		
15.1	11.1 > Reproductive toxicity	Added		
15.1	11.1 > Expected Symptoms/Effects, Acute and Delayed	Removed		
15.1	11.1 > Symptoms/effects aftereye contact	Added		
15.1	15.3 > DSL and NDSL	Removed		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 03/05/2021

Version: 15.1



Information in this document is accurate to the best of our know ledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at:

https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/

The Trade Name referenced in section 1 is a trademark ow ned or used by the Lyondell Basell family of companies.